

HS118V2 hotel IP phone can satisfy most hotel rooms and even the application requirements, beside, it has good expansibility and clear characteristics of quality voice calls.

HS118V2 is a popular type IP Phone in hotel phones series, with modern design, functional, practical and voice clarity characteristics. It accomplished the powerful telephony features by cooperating with the communications platform, such as call transfer, hotline, voice mail, interruption-free, etc.

HS118V2 IP phones support defined 10 programmable keys ,and it can define according to the hotel different needs. such as hotel all kind of equipment sevice hotline (housekeeping, ticketing, switchboard, food and beverage, etc.), the hotel special features (alarm clock, voice mail, etc.)

Key Features

- Support 10 programmable keys.
- HD Voice: HD Codec, HD Speaker.
- WEB support Multi-language, e.g. Chinese, English, Russian, French etc.
- 2 SIP accounts.
- Support IEEE802.3af class 0(POE).
- Convenient and fast for Installation and maintenance Support HTTP/TFTP/Telnet/Auto provision, and TR069 centralization maintenance.
- Call hold, Call waiting, Call forward, Call return, Call transfer.

HS118V2 Technical Datasheet

Phone Features

2 SIP accounts, Hotline Call hold, Call waiting, Call forward, Call return, Redial, Mute, DND Call transfer (blind/busy/ask) Auto-answer, Speed dial, SMS, Voicemail Message Waiting Indication LED Tone scheme, Volume control Direct IP call without SIP proxy Ring tone selection/import/delete Phonebook, Black list, Hand-free indicator. Call history: Multi-Language Support switching SIP server & Second server; 10 programmable keys

Advanced Features

Flash keys function:

>During a call, press the flash key to enter th Network Features e transferred pattern with dial tone. The call SIP v1 (RFC2543), v2 (RFC3261) will be holding. >When transferring the dialing, pressing the mode: flash key can cancel the transferred function. SRTP voice encryption(RFC3711) The call still be holding. >Pressing the flash key can >LDAP phone book recover the on holding call **IP PBX System Integration** DND ; Forward synchronization Intercom, Paging, Music on hold Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection

Compatible with the

Codes and Voice Features

Wideband Codec: G.722 Narrowband codec: G.711µ/A, G.726, G.729AB,iLBC VAD, CNG, AEC, AGC, Full-duplex,

Security

802.1x, VLAN QoS (802.1pq), SRTP * Transport Layer Security (TLS)* Digest authentication using MD5/MD5-sess Secure configuration file via AES encryption* Encryption for configuration file* Phone lock for personal privacy protection Admin/User 2-level configuration mode , LLDP, 1x RJ-9 handset port CDP L2TP VPN tunneling protocol - added

SIP connection: Proxy mode & Peering Points Redundant server support NAT Traversal: STUN mode DTMF: In-Band, RFC2833, SIP Info, Auto HTTP/HTTPS Web Management IP Assignment: Static/DHCP/PPPoE Bridge/Router mode for PC port TFTP/DHCP/PPPoE client Telnet/HTTP/HTTPS server, DNS client, NAT/DHCP server Layer 3 ToS, DSCP

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS, TR069 optional Configuration: browser/phone/auto-provision Trace package and system log export

Physical Features

30keys, including 12 digital keys 10x programmable keys, 1x redial key,1x hold key,1x speaker key,1x flash key,1x mute key 1x message LED 1xRJ45 10/100M Ethernet ports Power over Ethernet ,IEEE 802.3af,class 0 Operating humidity: 10~95% Storage temperature: up to 60°C Power adapter: AC 100~240V input and DC 5V/1A output

Package Features

Qty/CTN: N.W/CTN: Carton Meas:

Certifications





ESCENE COMMUNICATION CO., LTD

Add: Floor 4 building C YueAn Industrial Park No.51 Huangcun Road Tianhe District, Guangzhou, China. Tel: (86)20-82320720

*these features are not available and blocked in firmware for products which are supplied to Russian Federation and EAC countries